



Scoreboard Specifications

Overall size: 6' (W) x 4' (H) x 4" (D)
Approximate Weight: 131 lbs
Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 5 Amps. Requires an earth ground connection.
Incoming Mains Power and Data Location: TOP of the Scoreboard .

14" LED Digits for TIME
10" LED Digits for HOME, GUEST
7" LED Digits for PERIOD
2" LED Dots

6" White Vinyl Lettering for HOME, GUEST
4" White Vinyl Lettering for PERIOD
3" White Vinyl Lettering for P, TO, B

- All LED digits include the following:
- * Shatter Resistant Lexan cover
 - * Conformal coating to protect from environmental conditions
 - * Surface Mount Technology LEDs allowing for wider viewing angle
 - *

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	6/29/2020

		<div><div><div>OES</div><div>SCOREBOARDS</div><div>Inc.</div></div><div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div></div>	
<div>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:</div>		DESCRIPTION	
OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.		OES ELECTRONIC SCOREBOARDS M5006ATXV	
TOLERANCE INFORMATION Dimensions are in Inches		SIZE B	REV A
Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30'		USE FOR REVIEW	
<div><div></div></div>		SCALE NTS	DRAWN BY MLI
		PAGE 1	OF 1