

Scoreboard Specifications

Overall size: 6' (W) x 6' (H) x 4" (D) Approximate Weight: 168lbs Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 5 Amps. Requires an earth ground connection. Incoming Mains Power and Data Location: TOP of the Scoreboard.

14" LED Digits for TIME10" LED Digits for HOME, GUEST7" LED Digits for PERIOD, TM FOULS, PLAYER FOULS2" LED Dots

5" White Vinyl Lettering for HOME, GUEST 4" White Vinyl Lettering for PERIOD, TM FOULS, PLAYER FOULS 3" White Vinyl Lettering for P, TO, B

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- * Surface Mount Technology LEDs allowing for wider viewing angle



Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005"

Angular ± 30'

DESCRIPTION						AUTHOR DATE			
NITIAL	DESIGN				0	ES	7/2/202	0	
VING THIS	B DRAWING AND	4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: ces@ces-inc.com							
TY RIGHTS TO THE MATERIAL RAWING INCLUDES UNPUBLISHED IEVELOPED BY OES, INC. AND AS D, REPRODUCED OR USED IN ANY TEN AUTHORIZATION FROM OES,		DESCRIPTION OES ELECTRONIC SCOREBOARDS M5006BTXV							
	THIRD ANGLE PROJECTIONS		FILENAME M5006BTXV		INIT DRAWING DATE 7/2/20			REV	
		В	USE FOR REVIEW					A	
5"		SCAL	F NTS	DRAWN BY	MLI		PAGE	1 OF 1	