

Overall size: 8' (W) x 4'5" (H) x 4" (D) Approximate Weight: 167 lbs Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection. Incoming Mains Power and Data Location: TOP of the Scoreboard.

14" LED Digits for TIME 10" LED Digits for HOME, GUEST, PERIOD 2" LED Dots


5" Electronic Team Names at 8 CH

4" White Vinyl Lettering for PERIOD 3" White Vinyl Lettering for P, TO, B

All LED digits include the following:

\* Shatter Resistant Lexan cover

- \* Conformal coating to protect from environmental conditions
- \* Surface Mount Technology LEDs allowing for wider viewing angle



REVISION

А

UES, INC. CLAIMS PROPERT DISCLOSED HEREIN. THIS DI PROPRIETARY MATERIAL DE SUCH IS NOT TO BE COPIED WAY WITHOUT PRIOR WRITT INC.

TOLERANCE INFORMATION Dimensions are in Inches

Fractional  $\pm$  1/16" Two Place Decimals  $\pm$  0.02" Three Place Decimals  $\pm$  0.005" Four Place Decimals  $\pm$  0.0005" Angular  $\pm$  30'

	<b>,</b>							
	1' [0.3m]							
DESCF	RIPTION					AUTHOR	DATE	
NITIAL	DESIGN					OES	6/29/20	)20
				Inc.	London, Tel: (51 Fax: (51	akie Road, ON, N6L 1P7 9) 652-5833 9) 652-3795		
VING THIS DRAWING AND TY RIGHTS TO THE MATERIAL DRAWING INCLUDES UNPUBLISHED EVELOPED BY OES, INC. AND AS D, REPRODUCED OR USED IN ANY TEN AUTHORIZATION FROM OES,		DESCRIPTION OES ELECTRONIC SCOREBOARDS M5008ATXE						
	THIRD ANGLE PROJECTIONS	SIZE B	FILENAME M5008ATXE USAGE USE FOR REVIEW			NG DATE <b>)</b>	REV A	
" 5"	$  \bigoplus \subset ]$			USE F(				
		SCAL	e NTS	DRAWN BY	MLI	PAG	E 1 OF 1	