



**Scoreboard Specifications**

Overall size: 9' (W) x 7'4 <sup>1</sup>/<sub>2</sub>" (H) x 4" (D)  
Approximate Weight: 269 lbs  
Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.  
Incoming Mains Power and Data Location: TOP of the Scoreboard

14" LED Digits for TIME, SCORE  
10" LED Digits for PERIOD, TM FOULS, PLAYER FOULS  
2" LED Arrows

5" Electronic Team Names at 8 CH  
3" Electronic Captions at 4 CH, 8 CH

4" White Vinyl Lettering for PERIOD  
3" White Vinyl Lettering for P, TO, B

- All LED digits include the following:
- \* Shatter Resistant Lexan cover
  - \* Conformal coating to protect from environmental conditions
  - \* Surface Mount Technology LEDs allowing for wider viewing angle
  - \*

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	7/1/2020

		<div><div><div>OES</div><div>SCOREBOARDS</div><div>Inc.</div></div><div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div></div>					
<u>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:</u>		DESCRIPTION					
OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.		OES ELECTRONIC SCOREBOARDS M5009BTXH					
TOLERANCE INFORMATION Dimensions are in Inches  Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30°	THIRD ANGLE PROJECTIONS 	SIZE	FILENAME M5009BTXH	INIT DRAWING DATE 7/1/20	REV		
		B	USE FOR REVIEW			A	
		SCALE	NTS	DRAWN BY	MLI	PAGE	1 OF 1