

Scoreboard Specifications

Overall size: 9' (W) x 7'4 $\frac{1}{2}$ " (H) x 4" (D)

Approximate Weight: 260 lbs

Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.

Incoming Mains Power and Data Location: TOP of the Scoreboard

14" LED Digits for TIME, SCORE

10" LED Digits for PERIOD, TM FOULS, PLAYER FOULS

7" LED Digits for TOL

2" LED Arrows

5" Electronic Team Names at 8 CH

4" White Vinyl Lettering for PERIOD, TM FOULS, PLAYER FOULS, MATCH, POINTS

3" White Vinyl Lettering for P, TO, B, TOL

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- * Surface Mount Technology LEDs allowing for wider viewing angle



NOTICE TO PERSON RECEIVING THIS DRAWING AND

OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES,

TOLERANCE INFORMATION Dimensions are in Inches

Fractional ± 1/16"
Two Place Decimals ± 0.02"
Three Place Decimals ± 0.005"
Four Place Decimals ± 0.0005"

THIRD ANGLE PROJECTIONS

OES ELECTRONIC SCOREBOARDS
M5009CTXE

Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com

SIZE FILENAME M5009CTXE INIT DRAWING DATE 7/1/20 A

USAGE USE FOR REVIEW

SCALE NTS DRAWN BY MLI PAGE 1 OF 1