

Scoreboard Specifications

Overall size: 9' (W) x 7'4 1/2" (H) x 4" (D)
Approximate Weight: 279 lbs
Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.
Incoming Mains Power and Data Location: TOP of the Scoreboard



14" LED Digits for TIME, SCORE
10" LED Digits for PERIOD, TM FOULS, PLAYER FOULS
7" LED Digits for TOL
2" LED Arrows

5" Electronic Team Names at 8 CH
3" Electronic Captions at 4 CH, 8 CH

4" White Vinyl Lettering for PERIOD
3" White Vinyl Lettering for P, TO, B

- All LED digits include the following:
- * Shatter Resistant Lexan cover
 - * Conformal coating to protect from environmental conditions
 - * Surface Mount Technology LEDs allowing for wider viewing angle
 - *

| REVISION | | DESCRIPTION | AUTHOR | DATE |
|----------|--|----------------|--------|----------|
| A | | INITIAL DESIGN | OES | 7/1/2020 |
| | | | | |

| | | | | | |
|---|--|---|--|---|----------|
| | | <div><div>Inc.</div></div> <div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div> | | | |
| | | | | | |
| <div>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:</div> <div>OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.</div> | | | | | |
| DESCRIPTION | | | OES ELECTRONIC SCOREBOARDS M5009CTXH | | |
| TOLERANCE INFORMATION Dimensions are in Inches | | THIRD ANGLE PROJECTIONS | SIZE B | FILENAME M5009CTXH INIT DRAWING DATE 7/1/20 USAGE USE FOR REVIEW | REV A |
| Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30° | |  | SCALE NTS DRAWN BY MLI PAGE 1 OF 1 | | |