



**Scoreboard Specifications**

Overall size: 8' (W) x 4'5" (H) x 4" (D)  
Approximate Weight: 170 lbs  
Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.  
Incoming Mains Power and Data Location: TOP of the Scoreboard  
MAX Current Draw: 5.6 Amps

14" LED Digits for TIME  
10" LED Digits for HOME, GUEST, PERIOD  
2" LED Dots

5" Electronic Team Names at 8 CHARACTERS

4" White Vinyl Lettering for PERIOD  
3" White Vinyl Lettering for P. TO. B

Optional AD space:  
LEFT: 24.5" (W) X 24" (H)  
RIGHT: 19.5" (W) X 24" (H)

- All LED digits include the following:
- \* Shatter Resistant Lexan cover
  - \* Conformal coating to protect from environmental conditions
  - \* Surface Mount Technology LEDs allowing for wider viewing angle

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	7/13/2021
		<div><div></div><div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div></div>	
		<div><div><div>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:</div><div>OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.</div><div><div>TOLERANCE INFORMATION Dimensions are in Inches</div><div>Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30°</div></div></div><div><div>THIRD ANGLE PROJECTIONS</div><div></div></div></div>	
		<div><div><div><div></div><div>DESCRIPTION</div><div>OES ELECTRONIC SCOREBOARDS M5008AICE</div></div><div><div>SIZE</div><div>FILENAME M5008AICE</div><div>INIT DRAWING DATE 7/13/21</div><div>REV A</div></div></div><div><div>USAGE</div><div>USE FOR REVIEW</div></div></div>	
		<div><div>SCALE</div><div>NTS</div><div>DRAWN BY CGTHOMPSON</div><div>PAGE 1 OF 1</div></div>	