



Scoreboard Specifications

Overall size: 9'11" (W) x 4'6" (H) x 4" (D)
Approximate Weight: 196 lbs
Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.
Incoming Mains Power and Data Location: TOP of the Scoreboard
MAX Current Draw: 5.6 Amps

10" LED Digits for TIME, SCORE
7" LED Digits for PERIOD, FOULS, TOL, PLAYER FOULS
2" LED Arrows

5" Electronic Team Names at 8 CHARACTERS

4" White Vinyl Lettering for PERIOD, FOULS, TOL, PLYR FOULS, POINTS, MATCH
3" White Vinyl Lettering for P, TO, B

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- * Surface Mount Technology LEDs allowing for wider viewing angle

| | | | | | |
|----------|--|----------------|--|--------|-----------|
| REVISION | | DESCRIPTION | | AUTHOR | DATE |
| A | | INITIAL DESIGN | | OES | 8/10/2021 |

NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:

OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.

TOLERANCE INFORMATION
Dimensions are in Inches

Fractional ± 1/16"
Two Place Decimals ± 0.02"
Three Place Decimals ± 0.005"
Four Place Decimals ± 0.0005"
Angular ± 30°

THIRD ANGLE PROJECTIONS

4056 Blakie Road,
London, ON, N6L 1P7
Tel: (519) 652-5833
Fax: (519) 652-3795
Email: oes@oes-inc.com

| | | | |
|---|-----------|-------------------|------------|
| DESCRIPTION | | | |
| OES ELECTRONIC SCOREBOARDS M5010AICE | | | |
| SIZE | FILENAME | INIT DRAWING DATE | REV |
| A | M5010AICE | 8/10/21 | A |
| USAGE | | USE FOR REVIEW | |
| SCALE | NTS | DRAWN BY | CCTHOMPSON |
| PAGE | | 1 OF 1 | |