



Scoreboard Specifications

Overall size: 9'11" (W) x 7'4 1/2" (H) x 4" (D)
Approximate Weight: 276 lbs
Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.
Incoming Mains Power and Data Location: TOP of the Scoreboard
MAX Current Draw: 5.6 Amps

14" LED Digits for TIME, SCORE
10" LED Digits for PERIOD, TM FOULS, PLAYER, FOULS, POINTS
7" LED Digits for TOL
2" LED Arrows

5" Electronic Team Names at 8 CHARACTERS

4" White Vinyl Lettering for PERIOD, TM FOULS, PLYR, FOULS, PTS, MATCH, POINTS
3" White Vinyl Lettering for P, TO, B, TOL

Optional AD space:
LEFT: 36" (W) X 23.25" (H)
RIGHT: 30" (W) X 23.25" (H)

- All LED digits include the following:
- * Shatter Resistant Lexan cover
 - * Conformal coating to protect from environmental conditions
 - * Surface Mount Technology LEDs allowing for wider viewing angle

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	7/13/2021
		<div><div></div><div><div>OES</div><div>SCOREBOARDS</div></div><div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div></div>	
		DESCRIPTION OES ELECTRONIC SCOREBOARDS M5010BICE	
SIZE	FILENAME M5010BICE	INIT DRAWING DATE 7/13/21	REV
A	USAGE USE FOR REVIEW		A
TOLERANCE INFORMATION Dimensions are in Inches Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30°		THIRD ANGLE PROJECTIONS 	
SCALE	NTS	DRAWN BY CGTHOMPSON	PAGE 1 OF 1