

Scoreboard Specifications

Overall size: 9’11" (W) x 7’4 1/2" (H) x 4" (D)
Approximate Weight: 258 lbs
Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 5 Amps. Requires an earth ground connection.
Incoming Mains Power and Data Location: TOP of the Scoreboard
MAX Current Draw: 2.9 Amps



14" LED Digits for TIME, SCORE
10" LED Digits for PERIOD, TM FOULS, PLAYER, FOULS, POINTS
7" LED Digits for TOL
2" LED Arrows

8" White Vinyl Lettering for HOME, GUEST
4" White Vinyl Lettering for PERIOD, TM FOULS, PLYR, FOULS, PTS, MATCH, POINTS
3" White Vinyl Lettering for P, TO, B, TOL

Optional AD space:
LEFT: 36" (W) X 24" (H)
RIGHT: 30" (W) X 24" (H)

- All LED digits include the following:
- * Shatter Resistant Lexan cover
 - * Conformal coating to protect from environmental conditions
 - * Surface Mount Technology LEDs allowing for wider viewing angle

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	8/9/2021

		 <div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div>	
<div>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION: OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.</div>		DESCRIPTION OES ELECTRONIC SCOREBOARDS M5010BICV	
TOLERANCE INFORMATION Dimensions are in Inches Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30°	THIRD ANGLE PROJECTIONS 	SIZE A	FILENAME M5010BICV INIT DRAWING DATE 8/9/21 USAGE USE FOR REVIEW
SCALE NTS	DRAWN BY CGTHOMPSON	PAGE 1	REV A