

Scoreboard Specifications

Overall size: 6' (W) x 3'6" (H) x 4" (D)

Approximate Weight: 123 lbs

Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 5 Amps. Requires an earth ground connection.

Incoming Mains Power and Data Location: ON TOP OF THE SCOREBOARD

MAX Current Draw: 2.9 Amps

14" LED Digits for TIME

10" LED Digits for SCORE

7" LED Digits for PERIOD

2" LED Dots



3.5" White Vinyl Lettering for HOME, GUEST

3" White Vinyl Lettering for PERIOD, P1, P2

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- * Surface Mount Technology LEDs allowing for wider viewing angle

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	10/8/2020

NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION: OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.		 4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com	
TOLERANCE INFORMATION Dimensions are in Inches Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30°		THIRD ANGLE PROJECTIONS 	
DESCRIPTION OES ELECTRONIC SCOREBOARDS M6006AICV		SIZE A	REV A
FILENAME M6006AICV		INIT DRAWING DATE 10/8/20	
USAGE USE FOR REVIEW			
SCALE NTS	DRAWN BY CGTHOMPSON		PAGE 1 OF 1