

Scoreboard Specifications

Overall size: 9' (W) x 3'10" (H) x 4" (D) Approximate Weight: 175 lbs Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection. Incoming Mains Power and Data Location: ON TOP OF THE SCOREBOARD. MAX Current Draw: 5.6 Amps

14" LED Digits for TIME, SCORE 10" LED Digits for PERIOD


2" LED Dots

5" Electronic Team Names at 8 CH

4" White Vinyl Lettering for PERIOD 3" White Vinyl Lettering for P1, P2

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- * Surface Mount Technology LEDs allowing for wider viewing angle



OES, INC. CLAIMS PROPERT DISCLOSED HEREIN. THIS DE

DISCLOSED HEREIN. THIS D PROPRIETARY MATERIAL DI SUCH IS NOT TO BE COPIED WAY WITHOUT PRIOR WRIT INC.

TOLERANCE INFORMATION Dimensions are in Inches

Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30'

DESCRIPTION					AUTHOR	DATE	
NITIAL	DESIGN				OES	10/8/20	20
VING THIS DRAWING AND TY RIGHTS TO THE MATERIAL DRAWING INCLUDES UNPUBLISHED EVELOPED BY OES, INC. AND AS D, REPRODUCED OR USED IN ANY TER AUTHORIZATION FROM OES.		4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com DESCRIPTION DESCRIPTION DESCRIPTION DESCRIPTION DESCRIPTION					
	THIRD ANGLE	SIZE	FILENAME M6009AICE		INIT DRAWIN 10/8/20	G DATE	REV
-	PROJECTIONS	A	USE FOR REVIEW			A	
5"	$\Psi \square$						