

Scoreboard Specifications


Overall size: 9'11" (W) x 4'11" (H) x 4" (D) Approximate Weight: 206 lbs Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 10 Amps. Requires an earth ground connection. Incoming Mains Power and Data Location: ON TOP OF THE SCOREBOARD. MAX Current Draw: 5.6 Amps

10" LED Digits for TIME, SCORE 7" LED Digits for PERIOD, PLYR, PENALTY, SOG

6" White Vinyl Lettering for HOME, GUEST 4" White Vinyl Lettering for PERIOD, PLYR, PENALTY, SOG

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- * Surface Mount Technology LEDs allowing for wider viewing angle



REVISION

DISCLOSED HEREIN. THIS DI PROPRIETARY MATERIAL DE SUCH IS NOT TO BE COPIED WAY WITHOUT PRIOR WRITT INC.

TOLERANCE INFORMATION Dimensions are in Inches

 $\begin{array}{l} Fractional \pm 1/16"\\ Two Place Decimals \pm 0.02"\\ Three Place Decimals \pm 0.005"\\ Four Place Decimals \pm 0.0005"\\ Angular \pm 30'\\ \end{array}$

ESCRIPTION					AUTHOR	HOR DATE		
NITIAL DESIGN					OES	10/9/2020		
/ING THIS	DRAWING AND	4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com						
Y RIGHTS TO THE MATERIAL RAWING INCLUDES UNPUBLISHED ZVELOPED BY OES, INC. AND AS P, REPRODUCED OR USED IN ANY TEN AUTHORIZATION FROM OES,		DESCRIPTION OES ELECTRONIC SCOREBOARDS M6010CICV						
	THIRD ANGLE	-	FILENAME M6010CICV		INIT DRAWIN 10/9/20	G DATE		
		A	USE FOR REVIEW			A		