

Scoreboard Specifications

Overall size: 23' (W) x 3'10" (H) x 4" (D) Approximate Weight: 329 lbs Incoming Mains Power: (1) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 10 Amps. Requires an earth ground connection. Incoming Mains Power and Data Location: ON TOP OF THE SCOREBOARD. MAX Current Draw: 5.6 Amps


14" LED Digits for TIME, SCORE 10" LED Digits for PERIOD, PENALTY, SOG

5" Electronic Team Names at 8 CH

6" White Vinyl Lettering for PERIOD 4" White Vinyl Lettering for PENALTY, SOG

All LED digits include the following:

- * Shatter Resistant Lexan cover
- Conformal coating to protect from environmental conditions *
- Surface Mount Technology LEDs allowing for wider viewing angle *



REVISION

DISCLOSED HEREIN. THIS E PROPRIETARY MATERIAL D SUCH IS NOT TO BE COPIEL WAY WITHOUT PRIOR WRIT

TOLERANCE INFORMATION Dimensions are in Inches

Fractional \pm 1/16" Two Place Decimals \pm 0.02" Three Place Decimals \pm 0.005" Four Place Decimals \pm 0.0005" Angular ± 30'

DESCR	RIPTION				AUTHOR	DATE	
NITIAL	DESIGN				OES	10/9/2020	
VING THIS DRAWING AND TY RIGHTS TO THE MATERIAL DRAWING INCLUDES UNPUBLISHED EVELOPED BY OES, INC. AND AS D, REPRODUCED OR USED IN ANY ITEN AUTHORIZATION FROM OES.		DES London Tel: (51 Fax: (51					
	THIRD ANGLE	SIZE	FILENAME M6023BICE		INIT DRAWIN 10/9/20	G DATE	REV
	PROJECTIONS	A USE FOR RE					A
5"	$ \Psi \square$	SCALE NTS DRAW COTHOMPSON PAGE 1 OF 1					