


Scoreboard Specifications

Overall size: 16' (W) x 4'-11" (H) x 6" (D)
Approximate Weight: 467 lbs
Incoming Mains Power:120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 7.19 Amps. Requires an earth ground connection.
Incoming Mains Power and Data Location: Behind the INNING Digit.

- 22" LED Digits for HOME, INNING, GUEST
- 4" LED Dots for BALL, STRIKE, OUT
- 2" LED Dots for H,E
- 12" White Vinyl Lettering for HOME, GUEST
- 9" White Vinyl Lettering for BALL, STRIKE, OUT, INNING
- 7" White Vinyl Lettering for H, E

- All LED digits include the following:
- * Shatter Resistant Lexan cover
 - * Conformal coating to protect from environmental conditions
 - * Surface Mount Technology LEDs allowing for wider viewing angle

REVISION		DESCRIPTION		AUTHOR	DATE
A		INITIAL DESIGN		OES	3/15/2021

		<div><div></div><div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div></div>			
		DESCRIPTION OES ELECTRONIC SCOREBOARDS M7116DUXV			
SIZE		FILENAME M7116DUXV		INIT DRAWING DATE 3/15/21	
B		USAGE USE FOR REVIEW			REV A
SCALE NTS		DRAWN BY CGTHOMPSON		PAGE 1 OF 1	

<u>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:</u> OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.	
TOLERANCE INFORMATION Dimensions are in Inches Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30'	
THIRD ANGLE PROJECTIONS 