

Scoreboard Specifications

Overall size: 9' (W) x 4'-11" (H) x 6" (D)

Approximate Weight: 237 lbs

Incoming Mains Power: (1x) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.

Incoming Mains Power and Data Location: Behind the BALL ON Digit.

14" LED Digits for TIME, SCORE

10" LED Digits for BALL ON, QTR, DOWN, TO GO

8" White Vinyl Lettering for HOME, GUEST

6" White Vinyl Lettering for DOWN, TO GO, BALL ON, QTR

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- Surface Mount Technology LEDs allowing for wider viewing angle

	REVISION DESCRIPTION							DATE	
	A INITIAL DESIGN						OES	2/12/20	20
NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION: OES INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLIDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCES OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM CES.				London Tel: (51 Fax: (51					
	RANCE INFORMATION THIRD ANGLE sions are in Inches			FILENAME M8009AUXV	2/12/20		REV		
Two	nal ± 1/16" lace Decimals ± 0.02" Place Decimals + 0.005"		PROJECTIONS	A	USE FOR REVIEW			Α	
	Place Decimals ± 0.00 lar ± 30'	5"	SCALI	NTS	_{DRAW} Ç ₆ GTHOMF	SON PAGE	1 OF 1		