


Scoreboard Specifications


Overall size: 6' (W) x 3' (H) x 6" (D)
Approximate Weight: 159 lbs
Incoming Mains Power: (1x) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 5 Amps. Requires an earth ground connection.
Incoming Mains Power and Data Location: Behind the INNING Digit.

- 14" LED Digits for HOME, GUEST, INNING
- 2" LED Dots for BALL, STRIKE, OUT
- 4" White Vinyl Lettering for HOME, GUEST, INNING
- 3.5" White Vinyl Lettering for BALL, STRIKE, OUT

- All LED digits include the following:
- * Shatter Resistant Lexan cover
 - * Conformal coating to protect from environmental conditions
 - * Surface Mount Technology LEDs allowing for wider viewing angle

REVISION		DESCRIPTION		AUTHOR	DATE
A		INITIAL DESIGN		OES	5/12/2021

		<div><div></div><div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div></div>		
<div>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION: OES INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.</div>		DESCRIPTION <div>OES ELECTRONIC SCOREBOARDS M7106AxCV</div>		
SIZE	FILENAME M7106AUXV	INIT DRAWING DATE 5/12/21		REV
B	USAGE <div>USE FOR REVIEW</div>			A
SCALE	NTS	DRAWN BY MLI		PAGE 1 OF 1

TOLERANCE INFORMATION Dimensions are in Inches Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30'		THIRD ANGLE PROJECTIONS 
--	--	--