

Scoreboard Specifications



Overall size: 9' (W) x 4'-6" (H) x 6" (D)
Approximate Weight: 216 lbs
Incoming Mains Power: (1x) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.
Incoming Mains Power and Data Location: Behind the [INNING] Digit(s).

17" LED Digits for SCORE, INNING
4" LED Dots for BALL, STRIKE, OUT
2" LED Dots for H, E

6" White Vinyl Lettering for BALL, STRIKE, OUT, HOME, GUEST, INNING
5" White Vinyl Lettering for H, E

- All LED digits include the following:
- * Shatter Resistant Lexan cover
 - * Conformal coating to protect from environmental conditions
 - * Surface Mount Technology LEDs allowing for wider viewing angle

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	3/25/2021

				4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com	
<u>NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:</u> OES INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.		DESCRIPTION OES ELECTRONIC SCOREBOARDS M7109BxCV			
TOLERANCE INFORMATION Dimensions are in Inches Fractional $\pm 1/16"$ Two Place Decimals $\pm 0.02"$ Three Place Decimals $\pm 0.005"$ Four Place Decimals $\pm 0.0005"$ Angular $\pm 30^\circ$		SIZE	FILENAME M7109BUXV	INIT DRAWING DATE 3/25/21	REV
		B	USAGE	USE FOR REVIEW	
		SCALE	NTS	DRAWN BY MLI	PAGE 1 OF 1