

Scoreboard Specifications

Overall size: 9'11" (W) x 4'11" (H) x 6" (D)
Approximate Weight: 243 lbs
Incoming Mains Power: (1x) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 8 Amps. Requires an earth ground connection.
Incoming Mains Power and Data Location: Behind the [TIME] Digit(s).



17" LED Digits for ALL

8" White Vinyl Lettering for ALL

All LED digits include the following:

- * Shatter Resistant Lexan cover
- * Conformal coating to protect from environmental conditions
- * Surface Mount Technology LEDs allowing for wider viewing angle

REVISION		DESCRIPTION		AUTHOR	DATE
A		INITIAL DESIGN		OES	12/20/2021

		<div><div></div><div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div></div>			
		DESCRIPTION OES ELECTRONIC SCOREBOARDS M3010AxCV			
NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:					
OES INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.					
TOLERANCE INFORMATION Dimensions are in Inches		THIRD ANGLE PROJECTIONS			
Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30'					

SIZE	FILENAME M3010AUXV	INIT DRAWING DATE 12/20/21		REV
B	USAGE			A
USE FOR REVIEW				
SCALE NTS		DRAWN BY RDONALD		PAGE 1 OF 1