

**Scoreboard Specifications**

Overall size: 16' (W) x 6'-6" (H) x 6" (D)  
Approximate Weight: 623 lbs  
Incoming Mains Power: (1x) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 15 Amps. Requires an earth ground connection.  
Incoming Mains Power and Data Location: Behind the HALF Digit(s).



17" LED Digits for ALL

12" White Vinyl Lettering for HOME, GUEST  
7" White Vinyl Lettering for SHOTS, HALF

All LED digits include the following:

- \* Shatter Resistant Lexan cover
- \* Conformal coating to protect from environmental conditions
- \* Surface Mount Technology LEDs allowing for wider viewing angle
- \*

REVISION		DESCRIPTION		AUTHOR	DATE
A		INITIAL DESIGN		OES	5/12/2021

		<div><div></div><div>4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com</div></div>			
		DESCRIPTION OES ELECTRONIC SCOREBOARDS M4016AxCV			
NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:					
OES INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.					
TOLERANCE INFORMATION Dimensions are in Inches		THIRD ANGLE PROJECTIONS			
Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30'					

SIZE	FILENAME M4016AUXV	INIT DRAWING DATE 5/12/21		REV
B	USAGE			A
USE FOR REVIEW				
SCALE	NTS	DRAWN BY RDONALD		PAGE 1 OF 1