





**Scoreboard Specifications**  
Overall size: 25' (W) x 8' (H) x 6" (D)  
Approximate Weight: 983 lbs  
Incoming Mains Power: (1x) 120VAC (+/-10%) 1 Phase, 2 Wire, 60Hz / 20 Amps. Requires an earth ground connection.  
Incoming Mains Power and Data Location: Behind the C. KICKS Digit.

22" LED Digits for ALL  
6" LED Arrows

15" Whit Vinyl Lettering for HOME, GUEST  
12" White Vinyl Lettering for SHOTS, C. KICKS  
10" White Vinyl Lettering for 1ST HALF, 2ND HALF

This Layout is for internal reference only.  
All LED digits include the following:

- \* Shatter Resistant Lexan cover
- \* Conformal coating to protect from environmental conditions
- \* Surface Mount Technology LEDs allowing for wider viewing angle

REVISION	DESCRIPTION	AUTHOR	DATE
A	INITIAL DESIGN	OES	5/12/2021
NOTICE TO PERSON RECEIVING THIS DRAWING AND TECHNICAL INFORMATION:  OES, INC. CLAIMS PROPERTY RIGHTS TO THE MATERIAL DISCLOSED HEREIN. THIS DRAWING INCLUDES UNPUBLISHED PROPRIETARY MATERIAL DEVELOPED BY OES, INC. AND AS SUCH IS NOT TO BE COPIED, REPRODUCED OR USED IN ANY WAY WITHOUT PRIOR WRITTEN AUTHORIZATION FROM OES, INC.		4056 Blakie Road, London, ON, N6L 1P7 Tel: (519) 652-5833 Fax: (519) 652-3795 Email: oes@oes-inc.com	
TOLERANCE INFORMATION Dimensions are in Inches  Fractional ± 1/16" Two Place Decimals ± 0.02" Three Place Decimals ± 0.005" Four Place Decimals ± 0.0005" Angular ± 30°		THIRD ANGLE PROJECTIONS 	
SIZE	FILENAME	INIT DRAWING DATE	REV
A	M4025AUXV	5/12/21	A
DESCRIPTION OES ELECTRONIC SCOREBOARDS M4025AxCV			
USAGE USE FOR REVIEW			
SCALE	NTS	DRAWN BY CGTHOMPSON	PAGE 1 OF 1